

-Model E

Portable EV Charger

◆ Next-Level Safety

Revolutionary Triple-Shield Technology for Ultimate Charging Security

- **Charger:** Real-time data analysis and safety alerts ensure a secure charging environment.
- **Smart Charging:** Prevents overcharging and enhances battery safety.
- **Real-Time Monitoring:** Stops thermal runaway, keeping your battery safe.

◆ Long-Lasting Performance

Smart Battery Diagnostics for Extended Battery Life

- **Significantly Extends Battery Life:** Powered by our industry-leading AI algorithm.
- **Health Charging Mode:** Protects your EV battery and optimizes its lifespan.



◆ Bespoke Portable Charging Experience

Exclusive Features for Unmatched Charging Flexibility.

- **Cable Customization:** Design cables according to your unique needs and usage scenarios.
- **OLED Screen:** Check clear, real-time charging data on the sharp OLED display.
- **Current Adjustability:** Effortlessly modify the charging current to fit your vehicle's demands.

◆ Unmatched Reliability

Built to Withstand Extreme Conditions

- **IP65 Protection:** Resists dust, oil, and water, perfect for outdoor use.
- **Efficient Cooling:** Low failure rate even under heavy loads.
- **Thermal Runaway Prevention:** Ensures safety and reliability.

-Model E

Electrical Data

Input voltage/output voltage	110V / 220V / 380V AC
Adjustable current-1	3.7kW / 11kW: 6A-16A
Adjustable current-2	7.4kW / 22kW: 6A-32A
Adjustable current-3	9.6kW: 6A-40A
Max power	3.7kW / 7.4kW / 11kW / 22kW / 9.6kW
Cable length	5m / 7.5m cable / customized
Input frequency	50Hz / 60Hz
Charging connector	Type 1 / Type 2 / GB/T 20234 / NACS(Tesla)

Function

4G	Yes
Screen	OLED display
Power plug	Multiple plugs with temperature sensor
LED indicator light	√
Current adjustable	√
Delay start timer	√
Automatic recovery charging	√

Working Environment

Safety	12 safety protection built in
RCD	Type B, AC 30mA +DC 6mA
IP grade	IP 65
Environment temperature	-30°C~~+50°C

Guarantee

Warranty	2 years
Certificate	CE / TUV / CB / IT / RoHS / REACH / UKCA

Packing

Dimension	270*90*60mm
Holders	Including holders
Carry bag	Optional





12 Safety Protection

Vehicle Pulsating DC leakage Protection	√	Pressure Resistant Flame Retardant	√
Electrostatic Protection	√	Protecting Earthing Detection	√
Circuit Board Temp Sensor	√	Overcurrent Protection	√
Water-proof Protection	√	Crush Test	√
Intelligent Kernel	√	Overvoltage Protection	√
Undervoltage Protection	√	Lightning Protection	√

Multiple power plugs can be matched

Nema Series						
	Nema 5-15	Nema 6-20	Nema 10-30	Nema 10-50	Nema 14-50	
6A-16A Series						
	16A Schuko	UK Plug	AU Plug	SWISS T13	16A Blue CEE	16A Red CEE
10A-32A Series						
	32A Blue CEE	32A Red CEE				

Four types of connectors are available

Connectors				
	[Type 1] SAE J772	[Type 2] IEC 62196-2	[GB/T plug] GB/T 20234	[NACS plug]